

# PICKUP CLASS

## Tech Rules:

- Must have race receiver and needs to work
- All four brakes must lock up or won't race
- Front & rear tow chains must be present. No D-Rings allowed
- Possible drilling of bodies & frames for metal thickness
- Must have ball valve for vacuum on driver's side by front door post

## Race Officials will decide infraction of rules

## Protest Rule

- Must have protest in before driver's meeting or it will wait until next race
- \$50 per item you protest
  - Items: Carbs, Valve cover removal, spark plug removal, shocks, springs, body, suspension, etc...
- \$25 goes to tech and \$25 goes to protested car if found legal. \$25 will go to protestor if car is found to illegal.

## Number plate

- **3 sided number plate with 10" tall numbers – letters may appear behind number and must be at least 8" tall. NO four-digit number/letters allowed! Block letters recommended. NO OBSCENE WORDS OR CHARACTERIZATIONS OF ANY KIND ANYWHERE ON CAR.**
- **Must be black and white numbers! Either white number plate with black numbers or black number plate with white numbers. This is so the counters can easily read your number plates so you can be scored otherwise they will stop scoring you**
- **Please be sure your number is LEGIBLE so the scorer(s) can read it from where they are scoring**

## Body

- Any American made full-size 2 or 4 wheel drive pickup, Broncos, & Blazers
  - NO El Caminos, Ram Chargers, or Rancheros
- Body style must match frame
- Must have original steel firewall; cover as many holes in firewall as possible
- Must have steel under driver's seat and leg area
- Both doors must either be welded or bolted shut
- NO reinforcing of any kind to fender or box
- All body repairs must be made out of the same thickness of steel as original panel
- Must have a pickup box – NO flatbed, utility boxes or dump boxes – Does not have to have a complete floor in it
- Must have tailgate – Must be welded on

## Frame

- Stock pickup frames – must be same vintage as body
- No plating of frames unless frame is rusted through
- All frame repairs must be inspected by track inspectors and pass their approval

## Roll cage

- 4 point cage – MANDATORY
- Must have at least 3 door bars on driver's side
- Must have bars from cage to rear side of front A-arms
- May have steel plate on outside door bars, between bars and door skin
- Pad roll bars wherever needed
- Cage MUST be X'd behind driver
- Rear kickers ok

### **Suspension**

- Stock – front – arms - upper & lower
- Rear – if truck has leaf springs must run leaf springs. If truck has coil springs must run coil springs in stock location
- No suspension conversions
- Racing spring ok

### **Steering**

- Stock – no quick steer boxes

### **Drive Shaft**

- If 4 wheel drive – front drive shaft must be removed
- Must be painted white - Must have safety loop or chain 8"-10" behind transmission

### **Battery**

- Can be located in pickup bed behind cab or inside on passenger side securely fastened down with steel straps and covered – no ratchet straps or bungee cords

### **Wheels & Tires**

- Must use 1" lug nuts
- No bead locks
- Max wheel width 8"
- Any passenger car tire allowed
- Racing tires allowed
- NO LT tires allowed

### **Weight**

- Weight can be added to rear of truck but it must be either bolted in securely or welded securely – if bolted must be painted white

### **Radiator**

- Must be in stock location
- Aluminum radiators allowed
- Must have nerf bar in front of radiator – welded to bumper, no wider than frame. Nerf bar can be NO bigger than 1 ½" tubing – 2 bars up – 1 bar across – 2 bars going back to the frame in front of A-arm

### **Engine**

- Engines – stock
- May use different make of engine in truck (Example: Chevy-Ford, Ford – Chevy, Mopar – either)
- Cast iron factory heads
- No aluminum blocks – No aluminum heads
- Cast iron factory intakes
- After market 2bbl no bigger than 500 cfm
- OEM carburetor if 4bl. No after market
- Adaptor plates OK
- No roller rockers or roller tip rockers
- If running a fuel injected truck that truck MUST be a factory fuel injected one, and must have a fuel pump shut off switch in case of roll over
- Stock style ignition – NO MSD boxes
- Engine must carry 15" of vacuum at 900 RPS's
- Stock exhaust manifolds or headers – under vehicle
- Engine must be in stock location

- If using an aftermarket trans cooler – it must be mounted in engine compartment on firewall

### **Fuel Cells**

- Must be in bed of truck at middle to rear
- Must have rollover valve installed
- Must be a manufactured racing fuel cell with steel can around it
- Must be securely fastened down to angle iron or pipe between frame rails. Steel straps around fuel cell not just bolted to floor. No ratchet straps or bungee straps will be approved
- Fuel line must be inside of metal tubing from front to rear
- No larger than 16 gallon cell

### **Fuel**

- No racing, aviation or E-85 fuel. PUMP GAS ONLY

### **Bumpers**

- Front and rear tow hooks mandatory
- Must be a stock – factory pickup style bumper front and rear
- No ag hitches or trailer hitches
- NO pipe bumpers
- Must be securely bolted or welded securely on
- All four ends of bumper must be capped with no thicker than 1/8" thick metal and welded to body with metal be no taller than bumper
- Push bumper 1/12" tubing
  - No wider than frame rails
  - No higher than 14" from bumper
  - No kickers through core support

### **Rear Ends**

- Stock 9" ford, factory GM or Dodge
- Floater rear ends ok
- Can be welded posi

### **Brakes**

- All 4 brakes must work. Must lock upon inspection
- No aftermarket brake pedals

### **Shocks**

- Must be mounted in stock location – stock mounts
- Can be racing or stock shocks

### **Driver protection**

- Racing seat mandatory
- Fire suits MANDATORY – TOPS AND BOTTOMS. Gloves and racing shoes are recommended but not required.
- Must have 5 point safety harness
- Closed face helmet and neck roll required
- Must have window next (may do both sides)
- Must have 4 vertical bars in front of driver. Must cover from cage post to center of windshield – min 3/8" rod and covered with screen

**Remember: Build the pickup for driver safety**